

Cotswold Communications

24 way AC Mains Distribution Unit

Key Features

- Separately fused
- Individually monitored
- Live Supply in status
- Designation Strip
- Locking Power-con inputs
- IEC female outlets



Optional

- Female Power-Con outlets
- Dual Mains Input for supply Protection
- Sequential Start-up
- Master Supply Switch for anti-knock protection
- Load Amp Meter
- Power fail auto-notification
- 2 x Rear Tie Bars

24 way fused 6amp outlet with individual LED indicators. Power-con mains inlet. Should a fuse blow the individual outlet is indicated by changing from Green to Red. Fuses replaceable in seconds. Available with IEC or Power-con female outlets, dual supply input protection and anti-load sequential start-up. Front mains power On/Off available with anti-knock guard. Optional large Amp meter display and rear tie bars. Dual protection supply equipped with 9 Way D type second power failure remote alert.

Part no.	Type
P13014/F	Single Input
P13017/F	Dual Input with load meter
P13019/F	Dual Input Sequential Start

Please call for prices

Full Export services on request

Electrical

Supply AC 220/240 50Hz
Max Input 16 amp
Max output 6 amp

Mechanical

Height 2U (88mm)
Depth 256mm
Weight 3.3Kg

Construction

Case Aluminium
Finish Alocrom
Ground 4mm Stud

Telephone: 08452 307030

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.